

SmartCase™ SCR (USB) SmartCard based security

Issue August 2007

Pages 2

The Fujitsu Siemens Computers SmartCase™ SmartCard Reader (USB) facilitates the use of SmartCards. This USB SmartCard reader meets all the aspects of a modern security device: Security, Usability Reliability, and Ergonomics and of course, it is designed to meet all major standards and specifications. It provides an ideal platform for e-Commerce / e-Business, Public Key Infrastructure (PKI) applications, digital signature as well as SmartCard based authentication and access protection.

Fast data transfer from SmartCard to PC dedicates the SmartCase™ SCR (USB) to corporate security or SmartCard supported applications.

Security

- Use your SmartCard for secure PC access protection and store your login details in a safe place (Additional Software and SmartCard needed)
- Meet important standards like PC/SC specification and ISO 7816/1-4
- Microsoft PC 2001 compliant and "Designed for Microsoft"

Usability

- Seamless Plug & Play installation to every PC with USB interface
- Support of current operating systems' energy saving functions
- SystemLock support (BIOS Pre-Boot Protection)

Reliability

- High quality and function stability according to German standards
- Short reaction and transportation time
- Warranty, service and spare part supply according to your needs

Ergonomics

- Ergonomic considerations are consistently taken into account.
- Unique Fujitsu Siemens Computers design
- Long cable for convenient arrangement



SmartCase™ SCR (USB)	
Compliance	
Interface Standards	USB (compliant with USB 1.1 and 2.0) CCID (Microsoft) PC/SC CT-API ISO 7816, 1-4 HBCI (Homebanking Computer Interface)
EMC	CE (89/336/EEC) FCC Part. 15 Class B
Product Safety	UL 60950 CSA-C22.2 No. 60950
Certificates	Microsoft WHQL
Smartcard	
Protocols	T=0, T=1 2-wire (e.g. SLE4432, SLE4442) 3-wire (e.g. SLE4418, SLE4428) I ² C (Memorycards)
Card support	5V, 3V and 1,8V SmartCards
Card Contacting Unit	sliding, 100.000 insertion cycles
Transfer rate	with Host: 12 mBit/ sec with Card: 375 kBaud

Driver (PC/SC)	
Microsoft	MS Windows 2000 MS Windows XP
CT- API	Wrapper for MS Windows
Other operating systems	Linux (on request)
Driver Download	www.fujitsu-siemens.de/support/
Power consumption	
	over USB, max 50 mA
Operating temperature	15°C to 35°C
Dimensions (L/ W/ H)	80 x 60 x 25 mm
Weight	110 g
Design	
	Compact, dark grey transparent cabinet
Special Features	
	Duo-LED Status Indicator USB cable (1,8m) Adhesive mounting slider SystemLock
Package Contents	
	SmartCase™ SCR (USB) CD-Rom (driver & manual) Installation Guide